## **Uniform Mitigation Verification Inspection Form**

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: Apr 25, 2015
Owner Information
Owner Name: Embassy Park Condo Association Contact Person: Embassy Park Condo Association
Address: 1700 EMBASSY DRIVE 201 - 204 Home Phone: 561-900-4317
City: WEST PALM BECH Zip: 33401 Work Phone:
County: PALM BEACH Cell Phone:
Insurance Company: Policy #:
Year of Home: 1979 # of Stories: 2 Email: office@embassyparkwpb.com
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.
<ol> <li>Building Code: Was the structure built in compliance with the Florida Building Code (FBC 2001 or later) OR for homes located in the HVHZ (Miami-Dade or Broward counties), South Florida Building Code (SFBC-94)?</li> <li>A. Built in compliance with the FBC: Year Built For homes built in 2002/2003 provide a permit application with a date after 3/1/2002: Building Permit Application Date (MM/DD/YYYY)/</li></ol>
provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)//
2. <b>Roof Covering:</b> Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.
No Information  Permit Application FBC or MDC Year of Original Installation or Provided for  2.1 Roof Covering Type: Date Product Approval # Replacement Compliance
1. Asphalt/Fiberglass Shingle
2. Concrete/Clay Tile
3. Metal
4. Built Up
5. Membrane
6. Other TAR PITCH/GRAVEL
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.
□ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.
☐ C. One or more roof coverings do not meet the requirements of Answer "A" or "B".
☐ D. No roof coverings meet the requirements of Answer "A" or "B".
3. <b>Roof Deck Attachment</b> : What is the weakest form of roof deck attachment?
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.
B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.
C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of 24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR-Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent
Inspectors Initials MC Property Address 1700 EMBASSY DRIVE 201 - 204

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 1 of 1

found on the form

	-/	18	2 psf.	istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at leas
	¥			ed Concrete Roof Deck.
				or unidentified.
	_		No attic a	
4.	5 fe	eet o	of the insid	achment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)
		A.	Toe Nails	
				Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
				Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mi	nim	al conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:
				Secured to truss/rafter with a minimum of three (3) nails, and
				Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter <b>and</b> blocked no more than 1.5" of the truss/rafter, <b>and</b> free of visible severe corrosion.
		B.	Clips	
				Metal connectors that do not wrap over the top of the truss/rafter, or
				Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails.
		C.	Single W	raps  Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D.	Double W	** •
				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
				Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
	$\checkmark$	E.	Structural	Anchor bolts structurally connected or reinforced concrete roof.
		F.	Other:	
		G.	Unknown	or unidentified
		Η.	No attic a	ccess
5.				What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall o over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		A.	Hip Roof	
		В.	Flat Roof	
	<b>√</b>	C.	Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.
•	Car		dawy Wa4a	w Designation of (CW/D) ( (story lead and shallown entropy lead to a grant of falter do not small for one of CW/D)
0.	Sec		SWR (als	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the gor foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
		B.	No SWR.	
		C.	Unknown	or undetermined.
In	spec	tor	s Initials _	MC Property Address 1700 EMBASSY DRIVE 201 - 204
*T	hic	veri	ification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

•	ening Protection Level Chart		Glazed O <sub>l</sub>	penings			Glazed enings
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		X	X	$\times$		X
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						·
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
N	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X				X	

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure
and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

A in the table above
☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
B.1. All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

- □ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
   □ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
   □ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above
   C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with
- plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

  C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

  C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in
  - C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials MC Property Address 1700 EMBASSY DRIVE 201 - 204

the table above

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of A with no documentation of compliance (Level N in the	answer "A", "B", or C" or sy		
• `	· · · · · · · · · · · · · · · · · · ·	T C1	1
<ul> <li>N.1 All Non-Glazed openings classified as Level A, B, C,</li> <li>N.2 One or More Non-Glazed openings classified as Level table above</li> </ul>			
☐ N.3 One or More Non-Glazed openings is classified as Le	vel X in the table above		
X. None or Some Glazed Openings One or more Glazed	zed openings classified and	Level X	in the table above.
MITIGATION INSPECTIONS MUST Section 627.711(2), Florida Statutes, prov	~		
Qualified Inspector Name:	License Type:  Home Inspect	or	License or Certificate #:
Michael Casella Inspection Company:	nome mspect	Phone:	HI 432
		5	661-479-1810
Qualified Inspector – I hold an active license as a	: (check one)		
Home inspector licensed under Section 468.8314, Florida Statutraining approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida Statutraining approved by the Construction Industry Licensing Board	d and completion of a proficience		
General, building or residential contractor licensed under Section 408.007, Fibric			
Professional engineer licensed under Section 471.015, Florida			
□ Professional architect licensed under Section 481.213, Florida			
Any other individual or entity recognized by the insurer as possiverification form pursuant to Section 627.711(2), Florida Statu	sessing the necessary qualificati	ons to pi	roperly complete a uniform mitigation
Individuals other than licensed contractors licensed under	Section 489.111, Florida S	Statutes.	or professional engineer licensed
under Section 471.015, Florida Statues, must inspect the st	tructures personally and n	ot throu	gh employees or other persons.
Licensees under s.471.015 or s.489.111 may authorize a di		es the r	<u>equisite skill, knowledge, and</u>
experience to conduct a mitigation verification inspection.			
(print name)	and I personally performe		•
contractors and professional engineers only) I had my emp	loyee ( ^^^^^^^		
and I agree to be responsible for his/her work,	(print name	or msp.	,
Qualified Inspector Signature:	Date: Apr 2	25, 201	5
An individual or entity who knowingly or through gross no			
subject to investigation by the Florida Division of Insuran			
appropriate licensing agency or to criminal prosecution. (sertifies this form shall be directly liable for the miscondu			
performed the inspection.	et of employees as if the at	itiioi ize	u mitigation inspector personany
	17 . 11 1		
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification			
Signature:	Date: Apr 25, 2015		
An individual or entity who knowingly provides or utters	a false or fraudulent mitiga	tion ve	rification form with the intent to
obtain or receive a discount on an insurance premium to v			
of the first degree. (Section 627.711(7), Florida Statutes)			
The definitions on this form are for inspection purposes or as offering protection from hurricanes.	nly and cannot be used to c	ertify a	ny product or construction feature
Inspectors Initials <u>MC</u> Property Address 1700 EMBASS	Y DRIVE 201 - 204		
*This verification form is valid for up to five (5) years pro inaccuracies found on the form.	vided no material changes	have be	een made to the structure or

Page 4 of 4

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



**ROOF ELEVATION** 



**ROOF ELEVATION** 

## **ROOF ELEVATION**

Permit Number	01031141	Property ID	74434317180000000
Permit Desc	RFG	Balance Due	\$0.00
Property Address	1700 EMBASSY DR 201-204	Status	Closed
Permit   Plan F	Reviews   Inspections   F	ees   Contractors	All
THE REAL PROPERTY.		PERMIT	
PERMIT I	NFORMATION		
Application Date	2001-03-27	Operator	aneil
ssued Date	2001-03-27	Operator	aneil
Master Number		Project Number	
C.O. Number		Operator	
C.O. Issued			
		Usage Class	NONE
C-404 Type			
	11800	Units	0
C-404 Type Applied Value Calculated Value	11800		0 CCC013759
Applied Value Calculated Value PROPERT	0	Units	1000
Applied Value Calculated Value PROPERT Property ID	Y ON PERMIT	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext.	Y ON PERMIT	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address	O N PERMIT 74434317180000000	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address City	7 ON PERMIT 74434317180000000 1700 EMBASSY DR 201-204	Units	1000
Applied Value	7 ON PERMIT 7443431718000000 1700 EMBASSY DR 201-204 WEST PALM BEACH	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address City State Zip Code	ON PERMIT 74434317180000000 1700 EMBASSY DR 201-204 WEST PALM BEACH FL	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address City State Zip Code	74434317180000000 1700 EMBASSY DR 201-204 WEST PALM BEACH FL 33401	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address City State Zip Code DWNER O Name	Y ON PERMIT  74434317180000000  1700 EMBASSY DR 201-204 WEST PALM BEACH FL 33401  N PERMIT	Units	1000
Applied Value Calculated Value PROPERT Property ID Building Ext. Address City State Zip Code DWNER O	Y ON PERMIT  74434317180000000  1700 EMBASSY DR 201-204  WEST PALM BEACH FL 33401  N PERMIT  EMBASSY PARK CONDO ASSOC	Units	1000

## **ROOF PERMIT VERIFICATION**