## **Uniform Mitigation Verification Inspection Form**

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: Apr 25, 2015			
Owner Information			
Owner Name: Embassy Park Condo Associ	ciation	Contact Person: Embassy P	
Address: 1700 EMBASSY DRIVE 205 - 208	3	Home Phone: <b>561-90</b>	0-4317
City: WEST PALM BECH	Zip: <b>33401</b>	Work Phone:	
County: PALM BEACH		Cell Phone:	
Insurance Company:		Policy #:	
Year of Home: 1979	# of Stories: 2	Email: office@embassypar	kwpb.com
accompany this form. At least one photog	ating the compliance or existence of each c graph must accompany this form to validat I questions regarding the mitigated feature	e each attribute marke	d in questions 3
the HVHZ (Miami-Dade or Broward cou  ☐ A. Built in compliance with the FBC a date after 3/1/2002: Building Perm  ☐ B. For the HVHZ Only: Built in com	in compliance with the Florida Building Code (SFBC-9), South Florida Building Code (SFBC-9). For homes built in Application Date (MM/DD/YYYY)/////	94)? 1 2002/2003 provide a pe For homes built in 1	rmit application with 994, 1995, and 1996
	types in use. Provide the permit application of types in use. Provide the permit application was a		
	Application FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance
1. Asphalt/Fiberglass Shingle			
2. Concrete/Clay Tile			
_			
/		2001	
A. All roof coverings listed above m installation OR have a roofing perm	eet the FBC with a FBC or Miami-Dade Prodit application date on or after 3/1/02 OR the Dade Product Approval listing current at time	oof is original and built	in 2004 or later.
	1994 and before 3/1/2002 OR the roof is orig		
_	ot meet the requirements of Answer "A" or "I	3".	
☐ D. No roof coverings meet the require	rements of Answer "A" or "B".		
3. <b>Roof Deck Attachment</b> : What is the we	akest form of roof deck attachment?		
by staples or 6d nails spaced at 6" a	OSB) roof sheathing attached to the roof truss along the edge and 12" in the fieldOR- Bats, nails, adhesives, other deck fastening system or Options B or C below.	ten decking supporting	wood shakes or wood
24"inches o.c.) by 8d common nails other deck fastening system or truss	h a minimum thickness of 7/16" inch attached spaced a maximum of 12" inches in the field rafter spacing that is shown to have an equal rafter a mean uplift resistance of at least 103	lOR- Any system of scrivalent or greater resistat	ews, nails, adhesives,
24"inches o.c.) by 8d common nails decking with a minimum of 2 nails	h a minimum thickness of 7/16"inch attached spaced a maximum of 6" inches in the field. per board (or 1 nail per board if each board is ves, other deck fastening system or truss/rafte	-OR- Dimensional lumb equal to or less than 6 in	per/Tongue & Groove nches in width)OR-
Inspectors Initials MC Property Address	ss 1700 EMBASSY DRIVE 205 - 208		

\*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 1 of 1 found on the form

		18	2 psf.	istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at leas
	¥			d Concrete Roof Deck.
				or unidentified.
			No attic a	
	_			
4.	5 fe	eet o	of the insid	<b>achment:</b> What is the <b>WEAKEST</b> roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)
	Ш	A.	Toe Nails	
				Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
				Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mi	nim	al conditio	ons to qualify for categories B, C, or D. All visible metal connectors are:
				Secured to truss/rafter with a minimum of three (3) nails, and
				Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter <b>and</b> blocked no more than 1.5" of the truss/rafter, <b>and</b> free of visible severe corrosion.
		B.	Clips	
				Metal connectors that do not wrap over the top of the truss/rafter, or
				Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nai position requirements of C or D, but is secured with a minimum of 3 nails.
		C.	Single Wi	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D.	Double W	• • •
				Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
				Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
	$\checkmark$	E.	Structural	Anchor bolts structurally connected or reinforced concrete roof.
		F.	Other:	
		G.	Unknown	or unidentified
		H.	No attic a	ccess
5.				What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall o over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		A.	Hip Roof	
		В.	Flat Roof	
	<b>√</b>	C.	Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.
6	Soc		dawy Wata	w Desigtance (CWD), (standard underlayments on het manned felts de net quelify as an CWD)
0.	<b>▼</b>		SWR (als sheathing	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss.
		B.	No SWR.	noin water intraston in the event of foot covering loss.
				or undetermined.
In	spec	tor	s Initials _	MC_ Property Address 1700 EMBASSY DRIVE 205 - 208
*T	hic '	veri	ification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. <u>Opening Protection</u>: What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

•	ening Protection Level Chart		Glazed O	penings			Glazed enings
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		X	X	$\times$		$\times$
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X				X	

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure
and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

X in the table above
☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)
• SSTD 12 (Large Missile – 4 lb. to 8 lb.)
• For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.)
☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with

C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

Inspectors Initials MC Property Address 1700 EMBASSY DRIVE 205 - 208

☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

the table above

<sup>\*</sup>This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter protective coverings not meeting the requirements of A with no documentation of compliance (Level N in the	answer "A", "B", or C" or sy		
• `	<i>'</i>	I (1	1
<ul> <li>N.1 All Non-Glazed openings classified as Level A, B, C,</li> <li>N.2 One or More Non-Glazed openings classified as Leve table above</li> </ul>			
☐ N.3 One or More Non-Glazed openings is classified as Le	vel X in the table above		
X. None or Some Glazed Openings One or more Gla	zed openings classified and	Level X	in the table above.
MITIGATION INSPECTIONS MUST Section 627.711(2), Florida Statutes, prov	~		
Qualified Inspector Name:	License Type:  Home Inspect	or .	License or Certificate #:
Michael Casella Inspection Company:	Home mspect	Phone:	HI 432
		5	61-479-1810
Qualified Inspector – I hold an active license as a	: (check one)		
Home inspector licensed under Section 468.8314, Florida Statutraining approved by the Construction Industry Licensing Board Building code inspector certified under Section 468.607, Florida Statutraining approved by the Construction Industry Licensing Board	d and completion of a proficience		mber of hours of hurricane mitigation
<ul> <li>□ Building code inspector certified under Section 468.607, Floric</li> <li>□ General, building or residential contractor licensed under Section</li> </ul>			
Professional engineer licensed under Section 471.015, Florida			
Professional architect licensed under Section 4/1.013, Florida  Professional architect licensed under Section 481.213, Florida			
Any other individual or entity recognized by the insurer as possiverification form pursuant to Section 627.711(2), Florida Statu	sessing the necessary qualificati	ons to pi	operly complete a uniform mitigation
Individuals other than licensed contractors licensed under	· Section 480 111 Florida S	tatutes	or professional engineer licensed
under Section 471.015, Florida Statues, must inspect the s			
Licensees under s.471.015 or s.489.111 may authorize a di	rect employee who possess		
experience to conduct a mitigation verification inspection.	•		
(print name)	and I personally performe		
contractors and professional engineers only) I had my emp	loyee (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		
and I agree to be responsible for his/her_work,	(рини паше	oi ilispe	ector)
Qualified Inspector Signature:	Date: Apr	25 201	5
Quantieu inspector Signature:	Date: April	.5, 201.	<u></u>
An individual or entity who knowingly or through gross ne			
subject to investigation by the Florida Division of Insuran			
appropriate licensing agency or to criminal prosecution. (certifies this form shall be directly liable for the miscondu			
performed the inspection.	ict of employees as if the at	tiiorize	d mitigation inspector personany
Homeowner to complete: I certify that the named Qualifice residence identified on this form and that proof of identification			
Signature:	Date: Apr 25, 2015		
An individual or entity who knowingly provides or utters	a false or fraudulent mitiga	tion ve	rification form with the intent to
obtain or receive a discount on an insurance premium to v			
of the first degree. (Section 627.711(7), Florida Statutes)			
The definitions on this form are for inspection purposes of as offering protection from hurricanes.	nly and cannot be used to c	ertify a	ny product or construction feature
Inspectors Initials MC Property Address 1700 EMBASS	Y DRIVE 205 - 208		
*This verification form is valid for up to five (5) years pro inaccuracies found on the form.	vided no material changes	have be	een made to the structure or

Page 4 of 4

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



**ROOF ELEVATION** 



**ROOF ELEVATION** 

## **ROOF ELEVATION**

Permit Number	01040502	Property ID	74434317180000000
Permit Desc	RFG	Balance Due	\$0.00
Property Address	1700 EMBASSY DR 205/208	Status	Closed
Permit   Plan F	Reviews   Inspections   I	Fees   Contractors	All
Untilling-		PERMIT	
PERMIT I	NFORMATION		
Application Date	2001-04-11	Operator	aneil
Issued Date	2001-04-11	Operator	aneil
Master Number	11.1	Project Number	
C.O. Number		Operator	
C.O. Issued			And an own or service of the service
C-404 Type		Usage Class	NONE
Applied Value	11800	Units	0
Calculated Value	0	Contractor ID	CCC013759
PROPERT	Y ON PERMIT		
Property ID	74434317180000000		
Building Ext.			
Address	1700 EMBASSY DR 205/208		
	WEST PALM BEACH		
City			
	FL		
	FL 33401		
State Zip Code			
State Zip Code DWNER O	33401		
State Zip Code D W N E R O Name	33401 ON PERMIT		
State Zip Code  O W N E R O  Name  Address	33401 ON PERMIT EMBASSY PARK HOA	Туре	Private
200000000000000000000000000000000000000	33401 ON PERMIT EMBASSY PARK HOA 1700 EMBASSY DR	Type Zip Code	Private 33401
State Zip Code  O W N E R O  Name Address City State	33401  N P E R M I T  EMBASSY PARK HOA  1700 EMBASSY DR  WEST PALM BEACH FL	Zip Code	33401
State Zip Code  OWNER ON Name Address City State  MISCELL	33401  D N PERMIT  EMBASSY PARK HOA  1700 EMBASSY DR  WEST PALM BEACH	Zip Code	33401

